

SC300X

ALARM KIT FOR EMERGENCY SHOWERS



PRODUCT DESCRIPTION

- · Floor emergency eyewash equipment.
- · High water flow and low water pressure with total way out valve.
- · Instant automatic opening and closing activated by lateral lever or pedal.
- · Double aerated jet with dust cover.
- · Hand eyewash with wall support.
- · Suitable for industries, laboratories and generally where there is risk of personal damages from fire, acids, chemical reactants, petroleum products, radioactive materials or other contaminants.
- · CE conformity.


TECHNICAL DATA


- · Eyewash basin bowl Ø255mm made in stainless steel.
- · Manufactured in stainless steel.
- Connecting parts in stainless steel.
- · Water pressure, minimum 1.5 maximum 5 bar.
- Water inlet dimension: 1/2".
- · Outlet dimension: 1 1/4".



SC300X

TECHNICAL DRAWING





- 1) INGRESSO 1/2" G, FILETO FEMMINILE / ENTRADA 1/2 " G, ROSCA HEMBRA. 1/2" INCH G, INNER THREAD INLET / ENTRÉE 1/2" G, FILETAGE FEMELLE.
- 0055
- USCITA 11/4" G, FILETO FEMMINILE / SALIDA 1 11/4 " G, ROSCA HEMBRA. 1 11/4" G, OUTLET THREAD INLET / SORTIE 1 1/4" G, FILETATGE FEMELLE.
- 5 PAVIMENTO FINITO / SUELO ACABADO FINISHED FLOOR / SOL FINI

⁻ These specifications can be modified and/or rectified due to manufacture requirements.