
## SECUREMEN

## **Technical Data Sheet**

## Edge protection type G: 26 mm





Edge protection type G is a warning and protective bumper guard with the distinctive name Knuffi® that act as a personal crumple zone for people, machines and fixtures, absorb hard impacts and thus prevent injury or damage.

Profile body       Recyclable polyurethane foam         Surface       Polyurethane foam coloured by reverse printing and fixed in place by foaming so that no paint appears on outside         Adhesive       Profile body is affixed using light —and ageing-resistant high performance adhesive which has got an adhesion power of 21 N / 25 mm         Resistant to temperature       From -40 ° C to 100 °C         Classification       Fire Testing DIN EN 13501-1 / class E REACH 1907/2006 (33) & (67) RoHS 2011/65/EU & 2015/863         Colours       Bright yellow and black hatching as per ASR A1.3, red and white hatching as per ASR A1.3, black, white         Standard lengths       1 m, 5 m (shrinked in foil) and up to 50 m (in cardboard)         Installation       Simply adhere to clean, grease-free surfaces         Weight approx       1 m - 0,38 kg 5 m -1,99 kg 50 m - 19 kg		
by foaming so that no paint appears on outside  Adhesive Profile body is affixed using light —and ageing-resistant high performance adhesive which has got an adhesion power of 21 N / 25 mm  Resistant to From -40 ° C to 100 °C  Classification Fire Testing DIN EN 13501-1 / class E  REACH 1907/2006 (33) & (67)  RoHS 2011/65/EU & 2015/863  Colours Bright yellow and black hatching as per ASR A1.3, red and white hatching as per ASR A1.3, black, white  Standard lengths 1 m, 5 m (shrinked in foil) and up to 50 m (in cardboard)  Installation Simply adhere to clean, grease-free surfaces	Profile body	Recyclable polyurethane foam
performance adhesive which has got an adhesion power of 21 N / 25 mm  Resistant to temperature  Classification  Fire Testing DIN EN 13501-1 / class E  REACH 1907/2006 (33) & (67)  RoHS 2011/65/EU & 2015/863  Colours  Bright yellow and black hatching as per ASR A1.3, red and white hatching as per ASR A1.3, black, white  Standard lengths  1 m, 5 m (shrinked in foil) and up to 50 m (in cardboard)  Installation  Simply adhere to clean, grease-free surfaces	Surface	
temperature  Classification Fire Testing DIN EN 13501-1 / class E  REACH 1907/2006 (33) & (67)  RoHS 2011/65/EU & 2015/863  Colours Bright yellow and black hatching as per ASR A1.3, red and white hatching as per ASR A1.3, black, white  Standard lengths 1 m, 5 m (shrinked in foil) and up to 50 m (in cardboard)  Installation Simply adhere to clean, grease-free surfaces	Adhesive	performance adhesive which has got an adhesion power of 21 N /
REACH 1907/2006 (33) & (67) RoHS 2011/65/EU & 2015/863  Colours  Bright yellow and black hatching as per ASR A1.3, red and white hatching as per ASR A1.3, black, white  Standard lengths  1 m, 5 m (shrinked in foil) and up to 50 m (in cardboard)  Installation  Simply adhere to clean, grease-free surfaces		From -40 ° C to 100 °C
RoHS 2011/65/EU & 2015/863  Colours  Bright yellow and black hatching as per ASR A1.3, red and white hatching as per ASR A1.3, black, white  Standard lengths  1 m, 5 m (shrinked in foil) and up to 50 m (in cardboard)  Installation  Simply adhere to clean, grease-free surfaces	Classification	Fire Testing DIN EN 13501-1 / class E
Colours  Bright yellow and black hatching as per ASR A1.3, red and white hatching as per ASR A1.3, black, white  Standard lengths  1 m, 5 m (shrinked in foil) and up to 50 m (in cardboard)  Installation  Simply adhere to clean, grease-free surfaces		REACH 1907/2006 (33) & (67)
hatching as per ASR A1.3, black, white  Standard lengths 1 m, 5 m (shrinked in foil) and up to 50 m (in cardboard)  Installation Simply adhere to clean, grease-free surfaces		RoHS 2011/65/EU & 2015/863
Standard lengths 1 m, 5 m (shrinked in foil) and up to 50 m (in cardboard)  Installation Simply adhere to clean, grease-free surfaces	Colours	Bright yellow and black hatching as per ASR A1.3, red and white
Installation Simply adhere to clean, grease-free surfaces		hatching as per ASR A1.3, black, white
	Standard lengths	1 m, 5 m (shrinked in foil) and up to 50 m (in cardboard)
Weight approx 1 m - 0,38 kg 5 m -1,99 kg 50 m - 19 kg	Installation	Simply adhere to clean, grease-free surfaces
	Weight approx	1 m - 0,38 kg 5 m -1,99 kg 50 m - 19 kg
Shore Hardness Shore A = ca. 40	Shore Hardness	
	1	Specifications subject to change without notice, 02082020 MF

Specifications subject to change without notice. 02082020.MF